FILE NOTATIONS		
Entered in NID File	Checked by Chief	manuscal ding from
Entered On S R Sheet	Copy NID to Field Office	,
Location Map Pinned	Approval Letter	V
Card indexed	Disapproval Letter	****************
I W R for State or Fee Land		
COMPLETION DATA: Date Well Completed 7-29-58	Location Inspected	
OW WW TA	Bond released State of Fee Land	*******************
Driller's Log. 975 58 Electric Logs (No.)	FILED	i de la companya de
E	GR GR-N	Micro
Let MI-L Son	nic Others	Accession de la constantion de

Scout Report sent out	
Noted in the N!D File	ι
Location map pinned	6
Approval or Disapproval Letter	
Date Completed, P. & A. or operations suspended	
Fin changed on location map	
Affidavit and Record of A & P	
Water Shut-Off Test	
Gas-Oil Ratio Test	
Well Log Filed	



· (SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

9	Budget Bureau No. 42-R359.4. Approval expires 12-31-60.
	Indian Agency
	Navajo
₹	Allottee

NOTICE OF INTENTION	TO DRILL	X	CHECCHE	T DEBORT OF	E WATER CO.	T-OFF	
ł .	TO CHANGE PLANS		11			R ACIDIZING	1 1
1	TO TEST WATER SHUT-OFF		li .			ASING	
1	TO REDRILL OR REPAIR WEI		l)			OR REPAIR	1
NOTICE OF INTENTION			là .			NTT	1 1
1	TO PULL OR ALTER CASING		- 11				1 1
NOTICE OF INTENTION	TO ABANDON WELL						
	(1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-						
	(INDICATE ABOVE BY CI	ieck mark nat	Ture of Repo	rt, notice, o	R OTHER DAT	A)	
37 • B	. 10			May	22, 195	5 8	, 19
Navajo 1							
Well No. 1	is located 660	ft. from	S line a	_{nd} 660	_ft. from	$\{X_{V}\}$ line of	f sec. 35
SW SW Section			22E	SL		(**)	
(¼ Sec. and Sec. 1	No.) (Twp.)		lange)	(M	leridian)		
Gothic WC		San Ju	an		Uta	ah	
(Field)		(County or S	ubdivision)		(8)	tate or Territory)
The elevation of th	ne derrick floor abov	e sea level	ie	f. 460	4' Ungra	ded	
	io dollion liool abov	c sea level	13	_ 16.			
		DETAILS					,
(State names of and expec	eted depths to objective sand ing point	is; show sizes, v s, and all other	veights, and le r important p	ngths of prop roposed work	posed casings; ;)	indicate mude	ling jobs, cement-
to the surface with required be tested. Mu will be run be	se equipment will Surface Casing of Oil String: amount of cemen of Program: Converting caser hydraulic fra	: Approximed to Drill entional sing or a	imately amount of the stem To gel mud abandonm	900 of of of of of the of the of the of the officers of the of	8-5/8" OD smls ll oil a e used. timulati	OD casing casing of the casing	g cemented emented hows will closs etc
							·
I understand that this	plan of work must receive	approval in wri	ting by the G	sological Sur	vey before ope	erations may b	e commenced.
	The Carter Oil						
	Production Depa	rtment					
	Box 3082		÷	יאמת	V /a		
	Durango, Colorad	do		GUP	ORIGINAL SIGNED) B. M. Bi	RADLEY
~====				Ву			
				•		Bradley Superint	

CRIPTION			OUNTY	رک	BN	Jun	FN SE	C	35	т_ 5	40.S	_ R _	72E	ACR	ES
			NA	YA	<i>Jo</i> -	TR	AC.	7 4	18	# 1		PRO	Pos	€D	
necessary						FEI	ATHI	FRS.	ONE	- 5	TAN	ol int			
neet if nece		 2	7			\2	6			2	5				
k of this sheet if				CA	RT	E R		C	7.R.T	ER					
rred to tings (on back				CA	RT	€L			9R7						
Transfe List Fit	5	 ĕ	34			ن	75			- 3	6				
Coupled Fro	Signed				0,	Acres de la companya	Prop								w.5
<u> </u>		 CAR	TEK			,	927	EC-	60	.F		•,			
ken Up Screw, Welded o	t - Tulsa)		3			,	2			,	, 2		· · · · · · · · · · · · · · · · · · ·		
ize of Pipe Taken Painted District	Engineering Department			DESCRIBE OF STREET											
and Size	ineering D	 -			,.	1							• • • • • • • • • • •		
Total Length and Size of Pipe Taken Up Depth BuriedScrew, Date	\$									· · · · · · · · · · · · · · · · · · ·					
Total Deptl	(M					· ·									

Block Map Tr. (Pend.) ____Date___(Comp.) ____Date_

- 1

Sec	35	, T <u>40</u> \$	BOUTH	, R	22 E	ast s.	LaMa	
		WEST LIN	E.			6601	FROM	
Elevat	ion 460	LO UNIC	RADE	GROU	YD	••••••		
SAN	JUAN C	TTNUC			·	·	UTAE	ľ
	0 0 0							

			*******		<u>.</u>		******	
				5)				
	# 0 0 0 0 0		~					
	****						••••••	
66	oʻ.							N
<u>66</u>	660						•••••	
Scale-	-4 inches e	qual 1 mile			<u>:</u>			, ,
of act	s to certify ual surveys are true an	made by	me or u	ınder my	supervi:	sion and	that the	
		0-			Lea			
Seal:) R		Land S			
					P. LEES SG. NO.	1,7-		
Surve	/ed	3 MAY					19. 58	

Lease WAVAJO TRACT NO. 48-1 Well No.

May 28, 1958

The Carter Oil Company Production Department P. O. Box 3082 Durango, Colorado

Attention: B. M. Bradley, District Superintendent

Gentlemen:

This is to acknowledge receipt of your notice of intention to drill Well No. Navajo Treat 48-1, which is to be located 660 feet from the south line and 660 feet from the west line of Section 35, Township 40 South, Range 22 East, SLBM, San Juan County, Utah.

Please be advised that insofar as this office is concerned, approval to drill said well is hereby granted.

This approval terminates within 90 days if the above mentioned well is not spudded in within said period.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT SECRETARY

CBF: en

oc: Phil McGrath USGS, Farmington, New Mexico

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY


ALLOTTEE .				
TRIBE	Hav	ajo		
LEASE NO.	14-	20-60	3-278	,


LESSEE'S MONTHLY REPORT OF OPERATIONS // - |


The wells) fo	follor the	owing mon	is a th of		ours		ons and _, 19_58,	prod	uction (i	including	drilling and producin
Agent's			· .		P. O. Box	3082		Com	nexy	The Cart	er Oil Company
					Durango, C	olored	ø	Sign	PY To	IGNED]	HAS. C. JOHNSON
Phone					CH 7-0210			.—	t's title	Distri	ct Chief Clerk
SEC. AND 14 OF 14	Twp.	RANGE	WELL No.	DAYS PRODUCED	BARRELS OF OIL	GRAVITY	Cu. Fr. or (In thousan	447	Gallons of Gasoline Becovered	BARRELS OF WATER (If none, so state)	REMARKS (If drilling, depth; if shut down, cause date and result of test for gasoline content of gas)
ec. 35 W <i>SW</i>	Nav. Nos	jo 1 228	ract 1	148					er Service		Spudded 6-23-58 Drlg. 2957
	•										
		-									
	-										
									•		

runs or sales of gasoline during the month. (Write "no" where applicable.)

Note.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor.







LESSEE'S MONTHLY REPORT OF OPERATIONS

The vells) fo			4 1 1	, 	July		**	ons and _, 19 58 ,	pro	duction		drilling and produci
Agent's	addr	ess			P. O.	Bex	3082		Con	npany	The Cort	er Cil Company
					Durang	e, C	olorad	0	Sign	ned [DY ORIGINA	H. L. FARRIS
Phone .				(herry	7-0	200			ent's title	Was a	Formen
Sec. and H of H	TWP.	Range	Well No.	DAYS PRODUCED	BARREIS	оя Оп.	GRAVITY	Cv. Fr. or (in thousan	Gas ids)	GALLONS OF GASOLINE BECOVERED	BARRELS OF WATER (If none, so state)	(If drilling, depth; if shut down, can date and result of test for gasolin content of gas)
, 35 W	May:	ije 1 228	rect 1	1,8	1							Spudded 6-23-58 D&A 7-28-58
						*. *. ** * . !*						TD 5782
									*			
		,										
											en w	
	3							3 / 3 / 3 / 3 / 3 / 3 / 3 / 3 / 3 / 3 /	1 1 H			

runs or sales of gasoline during the month. (Write "no" where applicable.)

Note.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in

duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor. Form 9-329A (December 1948)

M. cu. ft. of gas sold;

35

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42~R359. Approval expires 12-31-60.
Indian Agency
Navajo

Allottee	
	14-20-603-27

M-1-50

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT.
		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u> </u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		1	lugust 4, 1958	19
Navajo Tract 48 Well No is located	d 660 ft	. from $\begin{cases} \mathbf{S} \\ \mathbf{S} \end{cases}$ line	and 660 ft. from	$\begin{Bmatrix} \mathbf{E} \\ \mathbf{W} \end{Bmatrix}$ line of sec. 35
SWSW Section 35	405	22E	SIM	•
(14 Sec. and Sec. No.) Gothic WC	(Twp.)	(Range) an Juan	(Meridian)	Utah
(Field)	(C	ounty or Subdivision)	(8:	tate or Territory)

The elevation of the derrick floor above sea level is _____ft. 4604!

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 5782' — It is intended to plug and abandon well as follows:

Place cement plugs — 31 sacks 5782-5682'; 46 sacks 5450-5300'; 31 sacks 4500-4400';

31 sacks 2450-2350'; 86 sacks 650-370'; 10 sacks 30' to surface, intervals
between plugs filled with drilling mud. To erect a 4" dry hole marker extending
4' above ground level, fill pits and clean location.

Verbal approval for above from Mr. P. T. McGrath 7-28-58.

I understand	that this plan of work must receive approval in writin	g by the Geological Survey before operations may be commenced.
Company	The Carter Oil Company Production Department	
O 011117 1111	Production Department	7
Address	Box 3082	CADY (ORIGINAL)
1 1001 0001	Durango, Colorado	COPY (ORIGINAL) H. L. FARRIS
		By
		H L Farris
		Title District Foreman

August 7, 1958

71-K 8-11-56

The Carter Oil Company Production Department P. O. Box 3082 Durango, Colorado

Attention: H. L. Farris, District Foreman

Bentlemen:

This is to asknowledge receipt of your notice of intention to abandon Well No. Navajo Traet 48-1, which is located 660 feet from the south line and 660 feet from the west line of Section 35, Township 40 South, Range 22 East, SLEM, San Juan County, Utah.

Please be advised that insofar as this office is concerned, approval to plug and abandon said well as per your notice is hereby granted.

Yours very truly,


OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT SECRETARY

CBF: co

cc: Phil McGrath





STATE OF UTAH OIL & GAS CONSERVATION COMMISSION

State Capitol Building Salt Lake City 14, Utah

То	be	kept	Confidential	until	
				(Not to exceed 4 months after filing dat	e

LOG OF OIL OR GAS WELL

_							-0	
-	_					s P. O. Box 30		
Lease	or Tract:	Navajo Ti	act 48		Field -	Gothic WC #8	State Utar	1
						·• M• Cou	•	
Locati	ion 6601	ft. $\left\{ \frac{N}{8x} \right\}$ of $\frac{1}{2}$	Line a	nd 660 f	t. [E.] of W	Line of Section	on 35 Eleve	ation 4634
\mathbf{T}	he inform	ation given l	nerewith is	s a compl	ete and correc	et record of the w		
so far		determined t	from all av		ecords.	But	adly	
Doto	Septem	er 12, 19	3 8			_	ist. Supt.	1
		1			~	l at above date.		
		- T	_			ned drillingJ		19 58
Comm	iencea ari	mmg1	4"					
	-	.	ن ۲۰	L.OR G	Denote gas by G)	OR ZONES D&	A July 29, 195	8
No. 1,	from	. 1	to			, from	to	
No. 2,	from		to		No. 5	, from	to	
		Į.				, from		
·		.	1	MPORT.	ANT WATER	SANDS	- 	
No. 1,	from		to		No. 3,	, from	to	
No. 2,	from		to		No. 4	, from	to	-g
ŕ	·				SING RECOI			•
Size	Weight	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated	Purpose
casing	per foot	<u> </u>					From+ To-	
3 – 3/8"	35.6	Weld 8-R		4031				
_5/8#∷	241()					1		I .
3-5/8"	24.0							
3-5/8"	24.0		-					
3 - 5/8#	24.0							
3 -5/8 **	24.0							
Size	Where s			DING AN				
Size		et Numi	MUDE	DING AN	ID CEMENTI	ING RECORD Mud gravity		
Size casing	Where s	et Numi	MUDE	DING AN	ID CEMENTI Method used	Mud gravity		
Size casing	Where s	et Numi	MUDE per sacks of ce	DING AN	D CEMENTI Method used Halliburton	Mud gravity		

	· · · · · · · · · · · · · · · · · · ·	SHO	OOTING R	ECORD			
Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned ou	t
]	í			(. (
- 1	j.				1		
Rotary tools	were used fro	m O [†] feet	to 57821	TD _{feet,}	and from	feet to	fee
		feet					
	·	19	DATES	t to prod	neing BRY I	HOLE	10
		e first 24 hours was					
		nd% sediment.					
If gas w	ell, cu. ft. per	24 hours	Gall	ons gasol	line per 1,000 cu	. ft. of gas	
Rock pr	ressure, lbs. pe	r sq. in	 EMPLOYE	ES			
		, Driller					Driller
		Driller				,	Driller
FBOM	то-	TOTAL FEE	MATION R	ECORD	FORMATIC	ON	
5581	انمولا	8421	Nava	jo ss.	Kayneta fm ar		
17100	2320	118:			nd Shinarump	•	
2320	21,20	100'		kopi fm	-	-0	
2420	2538	1181		elly ss			
2538	4438	1900'			* .	1.01	•
. –					n, cedar mesa	ss, and Rico	1m
14438	4850	1,121	Virg.				
4850	5108	2581	Misso	ouri			
5108 	5782	674	Des 1	<i>l</i> oines			
5565	5782	2171	Parac	iox			

[OVER]

VOD 75 MA

At the end or complete Uniter's 209, add Geologic Tops. State whether from Electric Logs or samples.

HISTORY OF OIL OR GAS WELL

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

NAVAJO TRACT 48 #1

CORES - #1 5412-51; recovered 39! and #2 5553-85; recovered 27½:

- DST #1 5374-5411, tool open two hours. Opened with good strong blow, gas to surface in 12 minutes at rate of 196 MCFPD and remained steady during test. Recovered 82 gas cut drilling mud and 10 thin muddy water.
 - #2 5525-52. Tool open two hours. Opened with immediate blow and died in 20 minutes. Recovered 35. oil and gas cut mud and 5. gas.
 - #3 5535-85. Tool open two hours. Tool opened with a fair blow throughout test. Recovered 67 slightly oil and gas cut mud.
 - #4 5665-5782. Tool opened with a very weak blow and died in 12 minutes. Bypass tool and had a blow for 10 minutes, bypassed tool again with slight blow. Recovered 37 mud.

Drilled to 5782;, dry and abandoned. Plugged well from 5782-5682; with 31 sacks cement; 5450 to 5300; with 46 sacks cement; 4500 to 4400; with 31 sacks cement; 2450 to 2350; with 31 sacks cement; 650 to 370; with 86 sacks cement and from 30; to 0; with 10 sacks cement. Installed dry hole marker with five sacks cement.

STATE OF UTAH DIVISION OF OIL, GAS AND MINING OIL AND GAS INSPECTION RECORD

OPERATOR:	HUMBLE OIL	3 REFINING CO		LEASE:	INDIAN
WELL NAME:				API:	43-037-10541
SEC/TWP/RNG:	35 40.0 S	22 . 0 E	CONTRACTOR:		
COUNTY:	SAN JUAN		FIELD NAME:		
DRILLING/COM	PLETION/WOR	KOVER:			
_ APD _ SAFETY _ OPERATIO	1000 (1000)	WELL SIGN POLLUTION ENTL OTHER	_ HOUSE! _ SURFA		_ BOPE _ PITS
SHUT-IN _	_				
WELL SIG	_	HOUSEKEEPING	_ EQUIP	MENT *	_ SAFETY
ABANDONED:	<u>Prikkraukinikanik</u>				
Y MARKER	Y	HOUSEKEEPING	Y REHAB		OTHER
PRODUCTION: _ WELL SIG _ METERING _ SECURITY		HOUSEKEEPING POLLUTION CNTL SAFETY	_ EQUIP _ PITS _ OTHER	MENT *	_ FACILITIES ? _ DISPOSAL
GAS DISPOSIT	ION:				
VENTED/F	LARED	SOLD	_ LEASE	JSE	
LEGEND: Y =	YES/SATISFA	CTORY N = NO/	UNSATISFACT	ORY A =	NOT APPLICABLE
*FACILITIES					
LOCATION AND	DRI MARKER				
REMARKS: P-A*D 5/28/5	8, TD 5782	, ALL OK.	adulia (d. 2 il. 1992), im lista sil 1 d	k de la la servação de la	er timber (v. 1700) stillbert ståb utbalk tide kikketting fal
ACTION:					
". VINSPECTOR: P.	AT DEGRUYTE	R	DATE:	*12/06/85	